WHAT IS CLAIMED IS

(Code Division Multiple Access)

- 1. A spreading method for use in a CDMA multi-rate system, comprising the steps of:
 - (A) coding message codes using Gray codes;
 - (B) generating a generating matrix, G_i , based on formed Gray codes; and
 - (C) multiplying the message coded by the Gray codes with the (Opthogonal Jacian) Factor) generating matrix for generating an OVSF codes with a specific length.
- The spreading method for use in a CDMA multi-rate system as claimed in claim 1, wherein said message is coded by a digital logic assembly circuit.
- 3. The spreading method for use in a CDMA multi-rate system as claimed in claim 2, wherein said digital logic assembly circuit is an encoder with a plurality of coefficients, and these coefficients are generated through the following matrix:

$$G_{i} = \begin{bmatrix} C_{2^{i}}^{(1,0,\dots,0)}(j_{i-1}) \\ C_{2^{i}}^{(0,1,0,\dots,0)}(j_{i-2}) \\ \vdots \\ C_{2^{i}}^{(0,\dots,0,1)}(j_{0}) \end{bmatrix}$$

4. The spreading method for use in a CDMA multi-rate system as

5

[I]

IJ

ΠJ

claimed in claim 1, further comprising the step of employing a multiplying circuit and said Gray codes are used as inputs of the encoder.

- 5. The spreading method for use in a CDMA multi-rate system as claimed in claim 1, wherein if extra Gray code label inputs are connected to "0" and extra output bits are discarded, a single encoding circuit is used to generate a short-length OVSF code in the code tree, thereby generating a whole OVSF code tree by storing a G_n , wherein n is the largest i.
- 6. A method for determining a mother code and a children code in a (Code Division Multiple Access)

 CDMA multi-rate system, comprising the steps of:

 (A) union a place little of Counciders to be be a least to the Counciders of Counciders to the control of the counciders to the control of the counciders to the councid
 - (A) using a plurality of Gray codes as labels of a plurality of OVSF codes; and
 - (B) determining whether a first OVSF code and a second OVSF code have a relation of a mother code and a children code by determining whether a label of said first OVSF code is a prefix of a label of said second OVSF code.
- 7. The method for determining a mother code and a children code in a CDMA multi-rate system as claimed in claim 6, wherein each OVSF code has a specific Gray code label, and wherein if an OVSF code is 0011, then a respective Gray code label is 01.
- 8. The method for determining a mother code or a children code in a CDMA multi-rate system as claimed in claim 6, wherein said Gray code labels serve to determine whether two OVSF codes have a relation of a mother code to a children code, assuming that said first

20

5

[] []10

OVSF code of 0011 has a Gray code label of 01, and said second OVSF code of 00111100 has a Gray code label of 010, and then said first OVSF code of 0011 is a mother code of said second OVSF code of 00111100.

of 00111100. (orthogonal labiable Spealing later Code Division Multiple Access)

9. A method for exchanging OVSF codes in a CDMA multi-rate

system, comprising the steps of:

- (A) using a plurality of Gray codes as labels of a plurality of OVSF codes;
- (B) performing a modulo-2 operation on the Gray code label of a first OVSF code and the Gray code label of a second OVSF code for generating a label of a third OVSF code; and
- (C) performing a modulo-2 operation on said third OVSF code and said first OVSF code for generating said second OVSF code.
- 10. The method for exchanging OVSF codes in a CDMA multi-rate system as claimed in claim 9, wherein each of said OVSF codes has a specific Gray code label.
- 11. The method for exchanging OVSF codes in a CDMA multi-rate system as claimed in claim 9, furthering comprising the step of employing a modulo-2 adder to generate said OVSF codes.

20